




Captive Panel Thumb Screws

slot drive - 303 stainless, blackened



Captive Screws



P0159.B2

CAPTIVE SCREWS

Material

Stainless steel (AISI 303, 1.4305), black oxide coating. Tensile strength 550 N/mm². Proof stress min. 190 N/mm², austenitic stainless steel. Also available on request in steel

(anodised, black oxide or zinc plated) stainless steel (AISI 316, 1.440), brass, aluminium etc.

Technical Notes

Used to comply with the Machinery Direc-

tive 2006/42/EC. Often used with our captive washers (P0168) or retaining flanges (P0169 - for sheet metal applications). The use of our captive washers should be considered when fitted in panels with unthreaded holes.

Order No.	d ₁	l ₁ ±0.25	d ₂ ±0.12	l ₂ ±0.25	d ₃	d ₄ min.	h ₁	h ₂	l ₃	l ₄	w ₁
P0159.030-010-B2	M 3	10	2	3.2	6.5	3.5	6.5	2.0	4.8	2.0	1.2
P0159.030-014-B2	M 3	14	2	3.2	6.5	3.5	6.5	2.0	8.8	2.0	1.2
P0159.030-016-B2	M 3	16	2	3.2	6.5	3.5	6.5	2.0	10.8	2.0	1.2
P0159.030-020-B2	M 3	20	2	3.2	6.5	3.5	6.5	2.0	14.8	2.0	1.2
P0159.030-022-B2	M 3	22	2	3.2	6.5	3.5	6.5	2.0	16.8	2.0	1.2
P0159.030-024-B2	M 3	24	2	3.2	6.5	3.5	6.5	2.0	18.8	2.0	1.2
P0159.030-026-B2	M 3	26	2	3.2	6.5	3.5	6.5	2.0	20.8	2.0	1.2
P0159.031-010-B2	M 3	10	2	3.2	8	3.5	8.0	2.0	4.8	2.0	1.2
P0159.031-014-B2	M 3	14	2	3.2	8	3.5	8.0	2.0	8.8	2.0	1.2
P0159.031-016-B2	M 3	16	2	3.2	8	3.5	8.0	2.0	10.8	2.0	1.2
P0159.031-020-B2	M 3	20	2	3.2	8	3.5	8.0	2.0	14.8	2.0	1.2
P0159.031-022-B2	M 3	22	2	3.2	8	3.5	8.0	2.0	16.8	2.0	1.2
P0159.031-024-B2	M 3	24	2	3.2	8	3.5	8.0	2.0	18.8	2.0	1.2
P0159.040-010-B2	M 4	10	3	5.5	8	4.5	8.0	2.0	2.0	2.5	1.2
P0159.040-014-B2	M 4	14	3	5.5	8	4.5	8.0	2.0	6.0	2.5	1.2
P0159.040-016-B2	M 4	16	3	5.5	8	4.5	8.0	2.0	8.0	2.5	1.2
P0159.040-020-B2	M 4	20	3	5.5	8	4.5	8.0	2.0	12.0	2.5	1.2
P0159.040-022-B2	M 4	22	3	5.5	8	4.5	8.0	2.0	14.0	2.5	1.2
P0159.040-024-B2	M 4	24	3	5.5	8	4.5	8.0	2.0	16.0	2.5	1.2
P0159.040-027-B2	M 4	27	3	5.5	8	4.5	8.0	2.0	19.0	2.5	1.2
P0159.040-032-B2	M 4	32	3	5.5	8	4.5	8.0	2.0	24.0	2.5	1.2
P0159.050-014-B2	M 5	14	3.5	6.5	10	5.5	10.0	2.5	3.5	4.0	1.5
P0159.050-016-B2	M 5	16	3.5	6.5	10	5.5	10.0	2.5	5.5	4.0	1.5
P0159.050-020-B2	M 5	20	3.5	6.5	10	5.5	10.0	2.5	9.5	4.0	1.5
P0159.050-022-B2	M 5	22	3.5	6.5	10	5.5	10.0	2.5	11.5	4.0	1.5
P0159.050-024-B2	M 5	24	3.5	6.5	10	5.5	10.0	2.5	13.5	4.0	1.5
P0159.050-027-B2	M 5	27	3.5	6.5	10	5.5	10.0	2.5	16.5	4.0	1.5
P0159.050-032-B2	M 5	32	3.5	6.5	10	5.5	10.0	2.5	21.5	4.0	1.5
P0159.050-035-B2	M 5	35	3.5	6.5	10	5.5	10.0	2.5	24.5	4.0	1.5
P0159.050-040-B2	M 5	40	3.5	6.5	10	5.5	10.0	2.5	29.5	4.0	1.5
P0159.060-016-B2	M 6	16	4.5	8.0	12	6.5	15.0	2.5	3.0	5.0	2.0
P0159.060-020-B2	M 6	20	4.5	8.0	12	6.5	15.0	2.5	7.0	5.0	2.0



Order No.	d ₁	l ₁ ±0.25	d ₂ ±0.12	l ₂ ±0.25	d ₃	d ₄ min.	h ₁	h ₂	l ₃	l ₄	w ₁
P0159.060-022-B2	M 6	22	4.5	8.0	12	6.5	15.0	2.5	9.0	5.0	2.0
P0159.060-024-B2	M 6	24	4.5	8.0	12	6.5	15.0	2.5	11.0	5.0	2.0
P0159.060-027-B2	M 6	27	4.5	8.0	12	6.5	15.0	2.5	14.0	5.0	2.0
P0159.060-032-B2	M 6	32	4.5	8.0	12	6.5	15.0	2.5	19.0	5.0	2.0
P0159.060-035-B2	M 6	35	4.5	8.0	12	6.5	15.0	2.5	22.0	5.0	2.0
P0159.060-040-B2	M 6	40	4.5	8.0	12	6.5	15.0	2.5	27.0	8.5	2.0
P0159.060-045-B2	M 6	45	4.5	8.0	12	6.5	15.0	2.5	32.0	8.5	2.0
P0159.060-050-B2	M 6	50	4.5	8.0	12	6.5	15.0	2.5	37.0	8.5	2.0