



R3242

RIGID COUPLINGS

Material

Stainless steel DIN 1,4305.

0,013mm.

Fasten component to hub with epoxy cement or stake and dutch pin.

Technical Notes

Diameters A & B are concentric within

Order No.	Bore dia. B	l	Ø A	Ø H	t
R3242.041	4	6	10	13	1.6
R3242.042	4	6	10	13	3.0
R3242.043	4	6	10	13	5.0
R3242.044	4	6	10	13	6.4
R3242.045	4	6	10	13	9.5
R3242.061	6	6	10	13	1.6
R3242.062	6	6	10	13	3.0
R3242.063	6	6	10	13	5.0
R3242.064	6	6	10	13	6.4
R3242.065	6	6	10	13	9.5
R3242.071	7	6	10	13	1.6
R3242.072	7	6	10	13	3.0
R3242.073	7	6	10	13	5.0
R3242.074	7	6	10	13	6.4
R3242.075	7	6	10	13	9.5
R3242.080	8	13	10	20	1.6
R3242.081	8	13	10	20	3.0
R3242.082	8	13	10	20	5.0
R3242.083	8	13	10	20	6.4
R3242.084	8	13	10	20	9.5
R3242.101	10	13	16	20	1.6
R3242.102	10	13	16	20	4.8
R3242.103	10	13	16	20	6.4
R3242.104	10	13	16	20	9.5
R3242.105	10	13	16	20	10.0
R3242.121	12	13	16	20	1.6
R3242.122	12	13	16	20	4.8
R3242.123	12	13	16	20	6.4
R3242.124	12	13	16	20	9.5
R3242.125	12	13	16	20	10.0